

## IEC Fuses

### Fuses maintenance set Set 5SF, 5ST, 5HF, 5HT



**Range 5SF - 5x20 - 250VAC**  
**Fast acting F - Low breaking capacity**  
**Reference number: G203763**  
**Catalog number: MIBOX5SF**

According to IEC-127-2 publication standard sheet 2



Breaking capacity under 250 VAC: 35 A or 10 I <sub>N</sub>					
<b>100 mA</b> A090505	<b>125 mA</b> B090506	<b>160 mA</b> C090507	<b>200 mA</b> D090508	<b>250 mA</b> E090509	<b>315 mA</b> F090510
<b>400 mA</b> G090511	<b>500 mA</b> H090512	<b>630 mA</b> J090513	<b>800 mA</b> K090514	<b>1 A</b> L090515	<b>1,25 A</b> M090516
<b>1,6 A</b> N090517	<b>2 A</b> P090518	<b>2,5 A</b> Q090519	<b>3,15 A</b> R090520	<b>4 A</b> S090521	<b>6,3 A</b> V090523

Max weight: 400 g

**Packaging:** 360 pieces (20x18)

**Range 5ST - 5x20 - 250VAC**  
**Time lag T - Low breaking capacity**  
**Reference number: H203764**  
**Catalog number: MIBOX5ST**

According to IEC-127-2 publication standard sheet 3



Breaking capacity under 250 VAC: 35 A or 10 I <sub>N</sub>					
<b>100 mA</b> F090533	<b>125 mA</b> G090534	<b>160 mA</b> H090535	<b>200 mA</b> J090536	<b>250 mA</b> K090537	<b>315 mA</b> L090538
<b>400 mA</b> M090539	<b>500 mA</b> N090540	<b>630 mA</b> P090541	<b>800 mA</b> Q090542	<b>1 A</b> R090543	<b>1,25 A</b> S090544
<b>1,6 A</b> T090545	<b>2 A</b> V090546	<b>2,5 A</b> W090547	<b>3,15 A</b> X090548	<b>4 A</b> Y090549	<b>6,3 A</b> A090551

Max weight: 400 g

**Packaging:** 360 pieces (20x18)

# Miniature Fuses

## IEC Fuses

### Fuses maintenance set

### Set 5SF, 5ST, 5HF, 5HT



**Range 5HF - 5x20 - 250VAC**  
**Fast acting F - High breaking capacity**  
**Reference number: B229863**  
**Catalog number: MIBOX5HF**

According to IEC-127-2 publication standard sheet 1



Breaking capacity under 250 VAC : 1500 A					
<b>100 mA</b> G095548	<b>125 mA</b> H095549	<b>160 mA</b> J095550	<b>200 mA</b> Q095556	<b>250 mA</b> R095557	<b>315 mA</b> S095558
<b>400 mA</b> T095559	<b>500 mA</b> V095560	<b>630 mA</b> W095561	<b>800 mA</b> X095562	<b>1 A</b> Y095563	<b>1,25 A</b> C095567
<b>1,6 A</b> D095568	<b>2 A</b> E095569	<b>2,5 A</b> F095570	<b>3,15 A</b> G095571	<b>4 A</b> H095572	<b>6,3 A</b> K095574

Max weight : 400 g

**Packaging:** 360 pieces (20x18)

**Range 5HT - 5x20 - 250VAC**  
**Time lag T - High breaking capacity**  
**Reference number: C229864**  
**Catalog number: MIBOX5HT**

According to IEC-127-2 publication standard sheet 5



Breaking capacity under 250 VAC : 1500 A					
<b>250 mA</b> P085366	<b>315 mA</b> R094821	<b>400 mA</b> W094825	<b>500 mA</b> S085369	<b>630 mA</b> X094826	<b>800 mA</b> V085371
<b>1 A</b> W085372	<b>1,25 A</b> X085373	<b>1,6 A</b> Y085374	<b>2 A</b> Z085375	<b>2,5 A</b> A085376	<b>3,15 A</b> B085377
<b>4 A</b> C085378	<b>5 A</b> D085379	<b>6,3 A</b> E085380	<b>8 A</b> A208357	<b>10 A</b> B208358	

Max weight : 400 g

**Packaging:** 360 pieces (20x18)