



ECF Quick Acting High Breaking Capacity

. 5 ϕ x 20 mm (0.197 x 0.787 inch)
 Ampere Rating: 63mA to 25 A
 Voltage Rating: 250V
Standards : IEC Standards
Option : Available Add Axial Leads
 Model No. **ECF-A**

Electrical Characteristics:

In	1.5 In		2.1 In		2.75 In		4 In		10 In
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Max.
63mA - 100mA	60 min	30 min	10 ms	2 sec	3 ms	300 ms	3 ms	300 ms	20 ms
125mA - 25A	60 min	30 min	10 ms	3 sec	3 ms	300 ms	3 ms	300 ms	20 ms



ECT Time-Lag High Breaking Capacity

. 5 ϕ x 20 mm (0.197 x 0.787 inch)
 Ampere Rating: 63mA to 25 A
 Voltage Rating: 250V
Standards : IEC Standards
Option : Available Add Axial Leads
 Model No. **ECT-A**

Electrical Characteristics:

In	1.5 In		2.1 In		2.75 In		4 In		10 In	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
63mA - 3.15A	60 min	30 min	200 ms	10 sec	40 ms	3 sec	10 ms	300 ms	300 ms	300 ms
4A - 25A	60 min	30 min	600 ms	10 sec	150 ms	3 sec	20 ms	300 ms	300 ms	300 ms



UNF Quick Acting Low Breaking Capacity

. 6.3 ϕ x 32 mm (1/4 x 1-1/4 inch)
 Ampere Rating: 50mA to 25 A
 Voltage Rating: 250V
Standards : IEC Standards
Option : Available Add Axial Leads
 Model No. **UNF-A**

Electrical Characteristics:

In	1.15In		2.1 In		2.75 In		4 In		10 In
	Min	Max	Min	Max	Min	Max	Min	Max	Max
50mA - 100A	60 min	20 sec	2 ms	200 ms	1 ms	30 ms	5 ms	5 ms	5 ms
125A - 25A	60 min	20 sec	20 ms	1.5 sec	8 ms	400 ms	80 ms	80 ms	80 ms



UNT Time-Lag Low Breaking Capacity

. 6.3 ϕ x 32 mm (1/4 x 1-1/4 inch)
 Ampere Rating: 50mA to 25 A
 Voltage Rating: 250V
Standards : IEC Standards
Option : Available Add Axial Leads
 Model No. **UNT-A**

Electrical Characteristics:

In	1.15 In		2.1 In		2.75 In		4 In		10 In	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
50mA - 2A	60 min	800 ms	20 sec.	150 ms	3 sec	60 ms	1 sec.	10 ms	200 ms	200 ms
2.5A - 25A	60 min	800 ms	30 sec.	200 ms	6 sec	80 ms	2 sec.	15 ms	300 ms	300 ms



UCF Quick Acting High Breaking Capacity

. 6.3 ϕ x 32 mm (1/4 x 1-1/4 inch)
 Ampere Rating: 100mA to 35 A
 Voltage Rating: 500V
Standards : IEC Standards
Option : Available Add Axial Leads
 Model No. **UCF-A**

Electrical Characteristics

In	1.5 In	2.1 In	4 In	10 In
	Min.	Max.	Max.	Max.
100mA - 35A	60 min	30 min	300ms	20ms



UCT Time-Lag High Breaking Capacity

. 6.3 ϕ x 32 mm (1/4 x 1-1/4 inch)
 Ampere Rating: 100mA to 25 A
 Voltage Rating: 500V
Standards : IEC Standards
Option : Available Add Axial Leads
 Model No. **UCT-A**

Electrical Characteristics

In	1.5 In		2.1 In		2.75 In		4 In		10 In	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
100mA~25A	60 min	30 min	600 ms	10 sec	200 ms	4 sec	50 ms	450 ms	450 ms	450 ms