




CONQUER

ELECTRONICS FUSES




GMX Medium Time Lag Glass Tube Fuses

. 5 ϕ x 25 mm (0.197 x 0.98 inch)
 Ampere Rating: 100mA to 20 A
 Voltage Rating: 250V and less
Electrical Characteristics:
 210% - 30 Minutes, **Maximum**
 400% - 0.3 Seconds, **Maximum**
 1000% - 5 mS Minimum
Standards: DIN 41576



GMJ Medium Time Lag Glass Tube Fuses

. 5 ϕ x 30 mm (0.197 x 1.18 inch)
 Ampere Rating: 100mA to 20 A
 Voltage Rating: 250V and less
Electrical Characteristics:
 210% - 30 Minutes, **Maximum**
 400% - 0.3 Seconds, **Maximum**
 1000% - 5 mS Minimum
Standards: DIN 41576



AWE AWP

AWE Fast Acting Glass Tube Fuses




6.3 ϕ x 22.2 mm (1/4 x 7/8 inch)
 Ampere Rating: 10mA to 30 A
 Voltage Rating: 250V and less
Electrical Characteristics:
 135% - 1 Hour, **Maximum**
 200% - 5 Seconds, **Maximum**
 Pig-Tail Lead(**AWP**): Tinned Copper Wire
 0.8 ϕ mm- < 13A
 1.0 ϕ mm- \geq 13A < 20A
 1.2 ϕ mm- \geq 20A
Standards: UL Listed 198G, CSA Certified
 C22.2N59



AAE AAP

AAE Fast Acting Glass Tube Fuses

6.3 ϕ x 15.9 mm (1/4 x 5/8 inch)
 Ampere Rating: 63mA to 30 A
 Voltage Rating: 250V and less
Electrical Characteristics:
 135% - 1 Hour, **Maximum**
 200% - 5 Seconds, **Maximum**
 Pig-Tail Lead(**AAP**): Tinned Copper Wire
 0.8 ϕ mm- < 13A
 1.0 ϕ mm- \geq 13A < 20A
 1.2 ϕ mm- \geq 20A

Approvals: AAP   
 3.5A and less, 125V






AXE Fast Acting For Instrument Glass Tube Fuses

6.3 ϕ x 25.4 mm (1/4 x 1 inch)
 Ampere Rating: 10mA to 30A
 Voltage Rating: 250V and less
Electrical Characteristics :
 135% - 1 Hour, **Maximum**
 200% - 10 Seconds, **Maximum**
Approvals    
 20A and less



AXP Fast Acting Glass Tube Fuses With Pig-Tail

6.3 ϕ x 25.4 mm (1/4 x 1 inch)
 Ampere Rating: 10mA to 30A
 Voltage Rating: 250V and less
Electrical Characteristics :
 135% - 1 Hour, **Maximum**
 200% - 10 Seconds, **Maximum**
 Pig-Tail Lead: Tinned Copper Wire
 0.8 ϕ mm- < 13A
 1.0 ϕ mm- \geq 13A < 20A
 1.2 ϕ mm- \geq 20A
Approvals   
 10A and less



GBF Very Fast Acting Ceramic Tube Fuses

. 5 ϕ x 20 mm (0.197 x 0.787 inch)
 Ampere Rating: 1 to 20 A
 Voltage Rating: 250V and less
Electrical Characteristics:
 135% - 2 Minutes, **Maximum**
 250% - 0.2 Seconds, **Maximum**
Recommend For Protection:
Solid-State Devices, Semiconductors



ABB Super Fast Acting Ceramic Tube Fuses

. 6.3 ϕ x 32 mm (1/4 x 1-1/4 inch)
 Ampere Rating: 1 to 30 A
 Voltage Rating: 500V and less
Electrical Characteristics:
 135% - 2 Minutes, **Maximum**
 250% - 0.2 Seconds, **Maximum**
Recommend For Protection:
Solid-State Devices, Semiconductors