





# CONQUER


## ELECTRONICS FUSES



### SMP Special 350V Fuse With Pig-Tail

4.5 $\phi$  x 14.5 mm  
 Ampere Rating: 10mA to 3.5A  
 Voltage Rating: 350V  
**Electrical Characteristics :**  
 135% - 1 Hour, **Maximum**  
 200% - 120 Seconds, **Maximum**  
**Interrupting Rating:** 100A, 300VAC  
 Pig-Tail Lead : 0.6 $\phi$  mm Copper Wire  
**Option :** Available on Tape and Reel  
**Option :** Transparent Heat Shrink Sleeve

**Approvals:** 




### CQ-WRI Insulating Fuses

**Supply With Insulating P.V.C. Tube**  
**These Fuses Are Designed For The Protection Of Electric And Electronic Appliances**

Fuses Ending Are Fully Insulated And Can Be Directly Wired To Circuits In Confined Areas Without Concern Of Electrical Contact

**Applicable For All Pig-Tail Type Fuses,**  
 To Order Just Add "WRI" e.g. GTP(WRI), AFP(WRI)




### ESF Quick Acting High Breaking Capacity

. 5 $\phi$  x 20 mm ( 0.197 x 0.787 inch )  
 Ampere Rating: 100mA to 20 A  
 Voltage Rating: 250V  
**Standards :** IEC Standards  
**Option :** Available Add Axial Leads  
 Model No. **ESF-A**

#### Electrical Characteristics:

In	1.5 In	2.1 In	4 In	10 In
	Min.	Max.	Max.	Max.
500mA - 6.3A	60 min	30 min	300ms	20ms




### ESM Medium Time-Lag High Breaking Capacity

. 5 $\phi$  x 20 mm ( 0.197 x 0.787 inch )  
 Ampere Rating: 100mA to 20 A  
 Voltage Rating: 250V  
**Standards :** IEC Standards  
**Option :** Available Add Axial Leads  
 Model No. **ESM-A**

#### Electrical Characteristics:

In	1.5 In	2.1 In	4 In		10 In	
	Min.	Max.	Min.	Max.	Min.	Max.
100mA - 20A	60 min	30 min	60ms	3s	5ms	300ms



### ENF Quick Acting Low Breaking Capacity

. 5 $\phi$  x 20 mm ( 0.197 x 0.787 inch )  
 Ampere Rating: 50mA to 25 A  
 Voltage Rating: 250V  
**Standards :** IEC Standards  
**Option :** Available Add Axial Leads  
 Model No. **ENF-A**

#### Electrical Characteristics:

In	1.5 In	2.1 In	4 In	10 In
	Min.	Max.	Max.	Max.
50mA - 25A	60 min	30 min	300ms	20ms



### ENT Time-Lag Low Breaking Capacity

. 5 $\phi$  x 20 mm ( 0.197 x 0.787 inch )  
 Ampere Rating: 50mA to 25 A  
 Voltage Rating: 250V  
**Standards :** IEC Standards  
**Option :** Available Add Axial Leads  
 Model No. **ENT-A**

#### Electrical Characteristics:

In	1.5 In	2.1 In	2.75 In		4 In		10 In	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
50mA - 25A	60 min	5 min	600ms	10 sec	150 ms	3 sec	20 ms	300 ms